



Product Specification

Product Name:

PORTER'S CONCRETE WASH

PRODUCT DESCRIPTION:

Porter's Concrete Wash is a semi-transparent coating that subtly colours and softens the appearance of interior concrete floors, exterior slabs, concrete pathways and pavers. Concrete Wash is designed to give a wash of colour, whilst highlighting the texture of the concrete, and if not treated with Porter's Clearcote, will gradually wear away, but can be refreshed when required.

LOCATION:

Interior or exterior.

ENVIRONMENTAL INFORMATION:

This product contains: 60g/L VOC.

APAS* Target level for this product: 80g/L.

Although this product is unique and there is no comparative product type, the closest comparison would be a typical one pack pigmented paving paint that has a VOC level of approx. 80g/L.

Porter's Paints use only premium grade, low odour, minimal environmental impact raw

materials, and wherever possible we buy from Australian suppliers. Our manufacturing processes are zero waste, and all paint formulations are designed for maximum performance with minimum impact on user health.

* Australian Paint Approval Scheme.

SUGGESTED APPLICATIONS:

Can be applied to bare concrete floors, pavers and slabs, polished or rough that are in sound condition.

COLOURS:

Choose from our large range of colours, or ask our colourist for your own custom colour.

LIMITATIONS:

Not suitable for use on driveways or car parking areas. Do not try to achieve greater opacity or depth of colour by the addition of further coats, as a build up of product can cause cracking and flaking of the finish. Do not apply in high humidity, below 10°C or above 30°C.

PREPARATION:

The substrate should be free of dust, oil, loose material and contaminants that may compromise adhesion. Where the surface is heavily soiled or contaminated with glues or oils, the substrate should be jet washed or acid etched prior to coating, and in some cases, may need to be ground. Fresh cementitious substrates should be cured for a minimum of 30 days.

APPLICATION:

Stir thoroughly prior to use. Apply Porter's Concrete Wash by brush. Wet Concrete Wash can be "ragged" for a more subtle effect. Can be thinned up to 100% with water. Touch dry 2 hours. Allow minimum 12 hours dry time before placing in service. Allow minimum 24 hours dry time before the application of Porter's Clearcote.

COVERAGE RATES:

Covers approximately 15-20m² per litre, depending upon porosity, surface texture and wastage rates.

WASH UP:

Water.

COMPLEMENTARY PRODUCTS:

Porter's Concrete Wash can be sealed and protected with Porter's Clearcote (coverage 15m² per litre). Allow Concrete Wash to dry for 24-72 hours before applying Clearcote. Test before use as a slight colour variation may occur.

PACKAGING:

Porter's Concrete Wash is available in 1 litre & 4 litre sizes.

STORAGE:

Store in a cool dry area, protected from frost.

PRECAUTIONS:

Keep out of reach of children. Avoid swallowing. Avoid eye contact. Avoid prolonged skin contact. Provide adequate ventilation. If accidental contact occurs, rinse immediately with water. Check colour before use.

WARRANTY:

Porter's Concrete Wash has a warranty of 7 years. Porter's Paints Pty Ltd warrants this product to be of the highest quality. The information supplied here is in good faith. There are no implied conditions or warranty in the supply of this product. The manufacturer's guarantee is limited to product replacement only and does not include preparation or application.

MANUFACTURER'S/DISTRIBUTOR'S DETAILS:

Porter's Paints Pty Ltd
895 Bourke St
Waterloo NSW 2017
Australia
Phone: (02) 9698-5322
Toll free: 1800 656 664
Fax: (02) 9699-5322
E-mail: enquiries@porters.com.au
Web: www.porterspains.com