



## Product Specification

Product Name:

# PORTER'S LOW SHEEN ACRYLIC

---

### PRODUCT DESCRIPTION:

Porter's Low Sheen Acrylic is a premium quality acrylic paint that gives exceptional coverage and intense colour. Fully washable - perfect for high traffic and family areas. This product is UV resistant, dirt resistant with almost no odour.

Australian suppliers. Our manufacturing processes are zero waste, and all paint formulations are designed for maximum performance with minimum impact on user health.

\* Australian Paint Approval Scheme.

Porter's Low Sheen Acrylic has met the assessment criteria set by Ecospecifier™ and is therefore eligible for Green Star credits. Please refer to [www.ecospecifier.com.au](http://www.ecospecifier.com.au) for further details.



### LOCATION:

Interior and exterior.

### SUGGESTED APPLICATIONS:

Can be applied to most suitably prepared plasterboard, plaster, wood, masonry and previously painted surfaces.

### ENVIRONMENTAL INFORMATION:

This product contains: <1g/L VOC.

### COLOURS:

Choose from our large range of colours, or ask our colourist for your own custom colour.

APAS\* Target level for this product: 5g/L.

### LIMITATIONS:

Porter's Paints use only premium grade, low odour, minimal environmental impact raw materials, and wherever possible we buy from

Do not apply in high humidity, below 10°C or above 30°C.

## PREPARATION:

### NEW/UNPAINTED SUBSTRATES:

Substrate should be a clean well-held surface free from loose material, dirt, grease, oil and mould. Dust down before proceeding.

On new unpainted plasterboard sheeting, render, brick or timber, spot prime all joints and repaired areas with Porter's Limeproof Undercoat Sealer, then apply two coats of same to entire area.

On new unpainted fresh set plaster do not proceed until plaster has thoroughly set and has dried completely. Firstly, apply 1 coat Porter's Mineral Silicate Primer by brush or roller. Touch dry 20 minutes. Allow 2 hours dry time. Then apply by brush, roller or spray 1 coat Porter's Limeproof Undercoat Sealer. Touch dry 2 hours. Allow 6 hours dry time.

### PREVIOUSLY PAINTED SUBTRATES:

Provided the surface is clean and sound, Porter's Low Sheen Acrylic is self-priming and can be applied directly over previously painted surfaces. (Except oil-based paints or polyurethanes). High gloss paints or varnishes should be sanded to remove gloss and create a "keyed" surface.

Surfaces painted with oil-based paints, or previously painted surfaces with loose, peeling or flaking paint must be made sound by scraping off loose paint. Fill nail holes and cracks with suitable filler, sand and dust off. Spot prime all joints and repaired areas with Porter's Limeproof Undercoat Sealer, then apply one coat to entire area. Touch dry two hours. Allow 6 hours dry time.

## APPLICATION:

Stir thoroughly prior to use. Apply two coats by brush, spray or a medium nap roller. Touch dry in 1 hour. Allow minimum 2 hours dry time between coats. Allow 6 hours dry time.

## COVERAGE RATES:

Covers approximately 12-14m<sup>2</sup> per litre, depending upon porosity, surface texture and wastage rates.

## WASH UP:

Water.

## COMPLEMENTARY PRODUCTS:

Porter's Limeproof Undercoat Sealer (coverage 12m<sup>2</sup> per litre) is recommended where an undercoat/primer is required when preparing substrate for painting.

Mineral Silicate Primer (coverage 10m<sup>2</sup> per litre) is recommended for priming new set plaster before undercoating.

## PACKAGING:

Porter's Low Sheen Acrylic is available in 1 litre, 4 litre, 10 litre & 15 litre sizes.

## STORAGE:

Store in a cool dry area, protected from frost.

## **PRECAUTIONS:**

Keep out of reach of children. Avoid swallowing. Avoid eye contact. Avoid prolonged skin contact. Provide adequate ventilation. If accidental contact occurs, rinse immediately with water. Check colour before use.

## **WARRANTY:**

Porter's Low Sheen Acrylic has a warranty for 15 years. Porter's Paints Pty Ltd warrants its products to be of the highest quality. The information supplied here is in good faith. There are no implied conditions or warranty in the supply of this product. The manufacturer's guarantee is limited to product replacement only and does not include preparation or application.

## **MANUFACTURER'S/DISTRIBUTOR'S DETAILS:**

Porter's Paints Pty Ltd  
895 Bourke St  
Waterloo NSW 2017  
Australia

Phone: (02) 9698-5322

Toll free: 1800 656 664

Fax: (02) 9699-5322

E-mail: [enquiries@porters.com.au](mailto:enquiries@porters.com.au)

Web: [www.porterspains.com](http://www.porterspains.com)