



Product Specification

Product Name:

PORTER'S TANNIN CHECK

PRODUCT DESCRIPTION:

Tannin is a water soluble stain that is present in many richly coloured timbers and tannin staining through water based paint systems can be a common problem. Porter's Tannin Check has been designed to be used as a **pre-treatment** to inhibit tannin migration. Timbers most prone to tannin staining include oregon, jarrah, merbau and western red cedar.

Particularly recommended prior to the application of Porter's Clearcote or Porter's Perfect Floor Paint on tannin rich timber. Also suitable to use *after* the application of Porter's Wood Wash, Palm Beach Black or Palm Beach White, prior to clear coating.

IMPORTANT NOTE:

It is essential that a test area is treated prior to larger areas being coated. Tannin is a natural substance found in timber, which can react with coatings to different degrees. We have experienced timbers that have no reaction at all, to the other end of the scale where 80 year old timbers contain tannins that are still very reactive and almost instantly create a heavy stain on any coatings. In cases such as the latter, Porter's Tannin Check should not be used. It is for this reason that we highly recommend testing first.

LOCATION:

Interior or Exterior

ENVIRONMENTAL INFORMATION:

This product contains: 53g/L VOC.

APAS* Target level for this product: 450g/L.

Porter's Paints use only premium grade, low odour, minimal environmental impact raw materials, and wherever possible we buy from Australian suppliers. Our manufacturing processes are zero waste, and all paint formulations are designed for maximum performance with minimum impact on user health.

* Australian Paint Approval Scheme.

SUGGESTED APPLICATIONS:

For use as a pre-treatment prior to painting or clear coating, over clean bare timber surfaces that are prone to tannin staining and that require these tannins to be sealed into the timber. Suitable to use *after* the application of Porter's Wood Wash, Palm Beach Black and Palm Beach White, prior to clear coating.

COLOUR:

Appears milky white in can, dries clear.

LIMITATIONS:

Not suitable for use over previously painted surfaces. This product is designed for use on bare timber surfaces, or surfaces finished with Porter's Wood Wash, prior to painting or clear coating. Do not apply in high humidity, below 10°C or above 30°C.

PREPARATION:

Substrate should be sanded to expose clean bare timber free from paint, dirt, grease, oil and previous coatings. Dust down before proceeding. Any surfaces newly finished with Porter's Wood Wash should be allowed minimum 12 hours to dry prior to application of Porter's Tannin Block.

APPLICATION:

Stir Tannin Check thoroughly prior to use. Apply one coat by brush, roller, spray or lamb's wool applicator. Touch dry 30 minutes. Allow to dry minimum 2 hours (or longer in colder or more humid conditions) before proceeding with chosen finish/painting.

COVERAGE RATES:

Covers approximately 5-7m² per litre, depending upon porosity, surface texture and wastage rates.

WASH UP:

Water.

PACKAGING:

Porter's Tannin Check is available in 1 litre, 4 litres & 10 litres.

STORAGE:

Store in a cool dry area, protected from frost.

PRECAUTIONS:

Keep out of reach of children. Avoid swallowing. Avoid eye contact. Avoid prolonged skin contact. Provide adequate ventilation. If accidental contact occurs, rinse immediately with water.

WARRANTY:

Porter's Paints Pty Ltd warrants its products to be of the highest quality. The information supplied here is in good faith. There are no implied conditions or warranty in the supply of this product. The manufacturer's guarantee is limited to product replacement only and does not include preparation or application.

MANUFACTURER'S/DISTRIBUTOR'S DETAILS:

Porter's Paints Pty Ltd
895 Bourke St
Waterloo NSW 2017
Australia
Phone: (02) 9698-5322
Toll free: 1800 656 664
Fax: (02) 9699-5322
E-mail: enquiries@porters.com.au
Web: www.porterspains.com