



Product Specification

Product Name:

PORTER'S ULTRA FLAT ACRYLIC

PRODUCT DESCRIPTION:

Porter's Ultra Flat Acrylic is a superb quality ultra matt acrylic paint that is designed to give a long lasting elegant finish with superior coverage (even in deep base) and beautiful depth of colour. The ultra matt finish plays down surface imperfections due to less reflection, as well as accentuating depth of colour. Suitable for use on ceilings. This product is UV resistant, mark resistant with almost no odour.



LOCATION:

Interior and exterior.

ENVIRONMENTAL INFORMATION:

This product contains: <1g/L VOC.

APAS* Target level for this product: 5g/L.

Porter's Paints use only premium grade, low odour, minimal environmental impact raw materials, and wherever possible we buy from Australian suppliers. Our manufacturing processes are zero waste, and all paint formulations are designed for maximum performance with minimum impact on user health.

* Australian Paint Approval Scheme.

Porter's Ultra Flat Acrylic has met the assessment criteria set by Ecospecifier™ and is therefore eligible for Green Star credits. Please refer to www.ecospecifier.com.au for further details.

SUGGESTED APPLICATIONS:

Can be applied to most suitably prepared plasterboard, plaster, wood, masonry and previously painted surfaces.

COLOURS:

Choose from our large range of colours, or ask our colourist for your own custom colour.

LIMITATIONS:

Do not apply in high humidity, below 10°C or above 30°C.

PREPARATION:

NEW/UNPAINTED SUBSTRATES:

Substrate should be a clean well-held surface free from loose material, dirt, grease, oil and mould. Dust down before proceeding.

On new unpainted plasterboard sheeting, render, brick or timber, spot prime all joints and repaired areas with Porter's Limeproof Undercoat Sealer, then apply two coats of same to entire area.

On new unpainted fresh set plaster do not proceed until plaster has thoroughly set and has dried completely. Firstly, apply 1 coat Porter's Mineral Silicate Primer by brush or roller. Touch dry 20 minutes. Allow 2 hours dry time. Then apply by brush, roller or spray 1 coat Porter's Limeproof Undercoat Sealer. Touch dry 2 hours. Allow 6 hours dry time.

PREVIOUSLY PAINTED SUBTRATES:

Provided the surface is clean and sound, Porter's Ultra Flat Acrylic is self-priming and can be applied directly over previously painted surfaces. (Except oil-based paint or polyurethanes). High gloss paints or varnishes should be sanded to remove gloss and create a "keyed" surface.

Surfaces painted with oil-based paints, or previously painted surfaces with loose, peeling or flaking paint must be made sound by scraping off loose paint. Fill nail holes and cracks with suitable filler, sand and dust off. Spot prime all joints and repaired areas with Porter's Limeproof Undercoat

Sealer, then apply one coat to entire area. Touch dry two hours. Allow 6 hours dry time.

APPLICATION:

Stir thoroughly prior to use. Apply two coats by brush, spray or a medium nap roller. Touch dry in 1 hour. Allow minimum 2 hours dry time between coats. Allow 6 hours dry time.

COVERAGE RATES:

Covers approximately 14-16m² per litre, depending upon porosity, surface texture and wastage rates.

WASH UP:

Water.

COMPLEMENTARY PRODUCTS:

Porter's Limeproof Undercoat Sealer (coverage 12m² per litre) is recommended where an undercoat/primer is required when preparing substrate for painting.

Mineral Silicate Primer (coverage 10m² per litre) is recommended for priming new set plaster before undercoating.

PACKAGING:

Porter's Ultra Flat Acrylic is available in 1 litre, 4 litre, 10 litre & 15 litre sizes.

STORAGE:

Store in a cool dry area, protected from frost.

PRECAUTIONS:

Keep out of reach of children. Avoid swallowing. Avoid eye contact. Avoid prolonged skin contact. Provide adequate ventilation. If accidental contact occurs, rinse immediately with water. Check colour before use.

WARRANTY:

Porter's Ultra Flat Acrylic has a warranty of 15 years. Porter's Paints Pty Ltd warrants its products to be of the highest quality. The information supplied here is in good faith. There are no implied conditions or warranty in the supply of this product. The manufacturer's guarantee is limited to product replacement only and does not include preparation or application.

MANUFACTURER'S/DISTRIBUTOR'S DETAILS:

Porter's Paints Pty Ltd
895 Bourke St
Waterloo NSW 2017
Australia

Phone: (02) 9698-5322

Toll free: 1800 656 664

Fax: (02) 9699-5322

E-mail: enquiries@porters.com.au

Web: www.porterspains.com